

Table 1 a

Dimensions
SUPERMAX, SUPERMAX2

Imperial Unit

Pipe Body					Pin	Coupling			Length in
Outside Diameter	Nominal Weight lbs/ft	Wall Thickness in	Inside Diameter in	Drift diameter in	Make up loss in	Regular Coupling OD in	Special Clearance		
							Special Clearance OD in	Joint Efficiency %	
in	lbs/ft	in	in	in	in	in	in	%	
2-3/8	4.60	0.190	1.995	1.901	2.848	2.875	2.700	119	6.596
	5.10	0.218	1.939	1.845			2.700	105	
	5.80	0.254	1.867	1.773			2.750	104	
2-7/8	6.40	0.217	2.441	2.347	2.912	3.500	3.250	118	6.724
	7.80	0.276	2.323	2.229			3.300	106	
3-1/2	7.70	0.216	3.068	2.943	3.162	4.250	3.850	113	7.224
	9.20	0.254	2.992	2.867			3.900	109	
	10.20	0.289	2.922	2.797			4.000	118	
4	9.50	0.226	3.548	3.423	3.242	4.750	4.400	120	7.434
	10.70	0.262	3.476	3.351			4.450	116	
	13.20	0.330	3.340	3.215			4.550	112	
	14.80	0.380	3.240	3.115			4.650	116	
4-1/2	10.50	0.224	4.052	3.927	3.492	5.000	4.900	124	7.934
	11.60	0.250	4.000	3.875			4.950	123	
	12.60	0.271	3.958	3.833			4.950	114	
	13.50	0.290	3.920	3.795		5.000	117		
	15.10	0.337	3.826	3.701		5.250	102		
5	15.00	0.296	4.408	4.283	4.102	5.563	5.375	90	9.204
	18.00	0.362	4.276	4.151			5.375	75	
	20.30	0.408	4.184	4.059			5.375	67	
5-1/2	15.50	0.275	4.95	4.825	4.102	6.050	5.875	96	9.204
	17.00	0.304	4.892	4.767			5.875	87	
	20.00	0.361	4.778	4.653			5.875	74	
6-5/8	20.00	0.288	6.049	5.924	4.352	7.390	7.000	94	9.704
	24.00	0.352	5.921	5.796			7.000	78	
	28.00	0.417	5.791	5.666			7.000	67	
7	23.00	0.317	6.366	6.241	4.352	7.875	7.375	86	9.704
	26.00	0.362	6.276	6.151			7.375	76	
	29.00	0.408	6.184	6.059			7.375	68	
	32.00	0.430	6.140	6.015			7.375	61	
7-5/8	26.20	0.328	6.969	6.844	4.652	8.500	8.125	107	10.304
	29.70	0.375	6.875	6.750			8.125	94	
	33.70	0.430	6.765	6.640			8.125	83	
	35.80	0.465	6.695	6.570			8.125	77	
	39.00	0.500	6.625	6.500			8.125	72	
8-5/8	32.00	0.352	7.921	7.796	4.752	9.625	9.125	101	10.504
	36.00	0.400	7.825	7.700			9.125	89	
	40.00	0.450	7.725	7.600			9.125	80	
9 5/8	36.00	0.352	8.921	8.765	4.852	10.625	10.125	101	10.704
	40.00	0.395	8.835	8.679			10.125	91	
	43.50	0.435	8.755	8.599			10.125	83	
	47.00	0.472	8.681	8.525			10.125	76	
	53.50	0.545	8.535	8.379			10.125	67	
10-3/4	40.50	0.350	10.050	9.894	4.902	11.750	11.250	103	10.804
	45.50	0.400	9.950	9.794			11.250	90	
	51.00	0.450	9.850	9.694			11.250	81	
	55.50	0.495	9.760	9.604			11.250	74	
13 3/8	54.50	0.380	12.615	12.459	4.977	14.375	-	-	10.954
	61.00	0.430	12.515	12.359			-	-	
	68.00	0.480	12.415	12.259			-	-	
	72.00	0.514	12.347	12.191			-	-	

Note : Joint Efficiency of Regular Coupling >=100%

Legal Notice

The use of this information is at the reader/user's risk and no warranty is implied or expressed by Metal One Corporation or its parents, subsidiaries or affiliates (herein collectively referred to as "Metal One") with respect to the use of information contained herein. The information provided on this Data Sheet is for informational purposes only, and was prepared by reference to engineering information that is specific to the subject products, without regard to safety-related factors, all of which are the sole responsibility of the operators and users of the subject connectors. Metal One assumes no responsibility for any errors with respect to this information.

Statements regarding the suitability of products for certain types of applications are based on Metal One's knowledge of typical requirements that are often placed on Metal One products in standard well configurations. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

The products described in this Data Sheet are not recommended for use in deep water offshore applications. For more information, please refer to http://www.mtlo.co.jp/mo-con/_images/top/WebsiteTerms_Active_20333287_1.pdf the contents of which are incorporated by reference into this Data Sheet.