

Table 1 b

Dimensions  
**SUPERMAX, SUPERMAX2**

Metric Unit

Pipe Body					Pin	Coupling			
Outside Diameter	Nominal Weight	Wall Thickness	Inside Diameter	Drift diameter	Make up loss	Regular Coupling OD	Special Clearance		Length
							Special Clearance OD	Joint Efficiency	
mm	Kg/m	mm	mm	mm	mm	mm	mm	%	mm
60.32	6.85	4.83	50.67	48.29	72.34	73.03	68.58	119	167.54
	7.60	5.54	49.25	46.87			68.58	105	
	8.64	6.45	47.42	45.04			69.85	104	
73.02	9.54	5.51	62.00	59.62	73.96	88.90	82.55	118	170.79
	11.62	7.01	59.00	56.62			83.82	106	
88.90	11.47	5.49	77.93	74.75	80.31	107.95	97.79	113	183.49
	13.71	6.45	76.00	72.82			99.06	109	
	15.20	7.34	74.22	71.04			101.60	118	
101.60	14.16	5.74	90.12	86.94	82.35	120.65	111.76	120	188.82
	15.94	6.65	88.29	85.12			113.03	116	
	19.67	8.38	84.84	81.66			115.57	112	
	22.05	9.65	82.30	79.12			118.11	116	
114.30	15.65	5.69	102.92	99.75	88.70	127.00	124.46	124	201.52
	17.28	6.35	101.60	98.43			125.73	123	
	18.77	6.88	100.53	97.36		133.35	125.73	114	
	20.12	7.37	99.57	96.39			127.00	117	
	22.50	8.56	97.18	94.01			127.00	102	
127.00	22.35	7.52	111.96	108.79	104.19	141.30	136.53	90	233.78
	26.82	9.19	108.61	105.44			136.53	75	
	30.25	10.36	106.27	103.10			136.53	67	
139.70	23.10	6.99	125.73	122.56	104.19	153.67	149.23	96	233.78
	25.33	7.72	124.26	121.08			149.23	87	
	29.80	9.17	121.36	118.19			149.23	74	
168.28	29.80	7.32	153.64	150.47	110.54	187.71	177.80	94	246.48
	35.76	8.94	150.39	147.22			177.80	78	
	41.72	10.59	147.09	143.92			177.80	67	
177.80	34.27	8.05	161.70	158.52	110.54	200.03	187.33	86	246.48
	38.74	9.19	159.41	156.24			187.33	76	
	43.21	10.36	157.07	153.90			187.33	68	
	47.68	10.92	155.96	152.78			187.33	61	
193.68	39.04	8.33	177.01	173.84	118.16	215.90	206.38	107	261.72
	44.25	9.53	174.63	171.45			206.38	94	
	50.21	10.92	171.83	168.66			206.38	83	
	53.34	11.81	170.05	166.88			206.38	77	
	58.11	12.70	168.28	165.10			206.38	72	
219.08	47.68	8.94	201.19	198.02	120.70	244.48	231.78	101	266.80
	53.64	10.16	198.76	195.58			231.78	89	
	59.60	11.43	196.22	193.04			231.78	80	
244.48	53.64	8.94	226.59	222.63	123.24	269.88	257.18	101	271.88
	59.60	10.03	224.41	220.45			257.18	91	
	64.82	11.05	222.38	218.41			257.18	83	
	70.03	11.99	220.50	216.54			257.18	76	
	79.72	13.84	216.79	212.83			257.18	67	
273.05	60.35	8.89	255.27	251.31	124.51	298.45	285.75	103	274.42
	67.80	10.16	252.73	248.77			285.75	90	
	75.99	11.43	250.19	246.23			285.75	81	
	82.70	12.57	247.90	243.94			285.75	74	
339.72	81.21	9.65	320.42	316.46	126.42	365.13	-	-	278.23
	90.89	10.92	317.88	313.92			-	-	
	101.32	12.19	315.34	311.38			-	-	
	107.28	13.06	313.61	309.65			-	-	

Note : Joint Efficiency of Regular Coupling &gt;=100%

## Legal Notice

The use of this information is at the reader/user's risk and no warranty is implied or expressed by Metal One Corporation or its parents, subsidiaries or affiliates (herein collectively referred to as "Metal One") with respect to the use of information contained herein. The information provided on this Data Sheet is for informational purposes only, and was prepared by reference to engineering information that is specific to the subject products, without regard to safety-related factors, all of which are the sole responsibility of the operators and users of the subject connectors. Metal One assumes no responsibility for any errors with respect to this information.

Statements regarding the suitability of products for certain types of applications are based on Metal One's knowledge of typical requirements that are often placed on Metal One products in standard well configurations. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. The products described in this Data Sheet are not recommended for use in deep water offshore applications. For more information, please refer to [http://www.mtlo.co.jp/mo-con/\\_images/top/WebsiteTerms\\_Active\\_20333287\\_1.pdf](http://www.mtlo.co.jp/mo-con/_images/top/WebsiteTerms_Active_20333287_1.pdf) the contents of which are incorporated by reference into this Data Sheet.