

Table 31 a

**Performance Properties
SUPERMAX-TS, SUPERMAX-TS2**

Imperial Unit

Pipe Body			Collapse			Internal yield pressure			Minimum Yield Load (for Regular Coupling)		
Outside Diameter	Nominal Weight	Wall Thickness	J55	L80 N80	P110	J55	L80 N80	P110	J55	L80 N80	P110
in	lbs/ft	in	psi	psi	psi	psi	psi	psi	kips	kips	kips
2 3/8	4.60	0.190	8,100	11,780	16,130	7,700	11,200	15,400	72	104	143
2 7/8	6.40	0.217	7,680	11,170	14,550	7,260	10,570	14,530	100	145	199
3 1/2	7.70	0.216	5,970	7,860	9,730	5,940	8,640	11,880	123	178	245
	9.20	0.254	7,400	10,540	13,530	6,980	10,160	13,970	142	207	285
	10.20	0.289	8,330	12,120	16,670	7,950	11,560	15,900	160	233	321
4	10.70	0.262	6,590	8,800	11,060	6,300	9,170	12,610	169	246	338
4 1/2	10.50	0.224	4,010	4,930	5,550	4,790	6,970	9,580	165	241	331
	11.60	0.250	4,950	6,350	7,570	5,350	7,780	10,700	183	267	367
	12.60	0.271	5,720	7,500	9,210	5,800	8,430	11,590	198	288	396
	13.50	0.290	6,420	8,540	10,690	6,200	9,020	12,410	211	307	422
	15.10	0.337	7,620	11,080	14,340	7,210	10,480	14,420	242	352	485
5	15.00	0.296	5,560	7,250	8,850	5,700	8,290	11,400	240	350	481
	18.00	0.362	7,390	10,500	13,470	6,970	10,140	13,940	290	422	580
5 1/2	15.50	0.275	4,040	4,990	5,630	4,810	7,000	9,630	248	361	496
	17.00	0.304	4,910	6,290	7,480	5,320	7,740	10,640	273	397	546
	20.00	0.361	6,620	8,830	11,110	6,320	9,190	12,630	320	466	641
6 5/8	20.00	0.288	2,970	3,470	4,030	4,180	6,090	8,370	315	458	630
	24.00	0.352	4,560	5,760	6,730	5,110	7,440	10,230	381	555	763
7	23.00	0.317	3,270	3,830	4,440	4,360	6,340	8,720	366	532	732
	26.00	0.362	4,330	5,410	6,230	4,980	7,240	9,950	415	604	830
	29.00	0.408	5,410	7,030	8,530	5,610	8,160	11,220	464	676	929

Legal Notice

The use of this information is at the reader/user's risk and no warranty is implied or expressed by Metal One Corporation or its parents, subsidiaries or affiliates (herein collectively referred to as "Metal One") with respect to the use of information contained herein. The information provided on this Data Sheet is for informational purposes only, and was prepared by reference to engineering information that is specific to the subject products, without regard to safety-related factors, all of which are the sole responsibility of the operators and users of the subject connectors. Metal One assumes no responsibility for any errors with respect to this information.

Statements regarding the suitability of products for certain types of applications are based on Metal One's knowledge of typical requirements that are often placed on Metal One products in standard well configurations. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. The products described in this Data Sheet are not recommended for use in deep water offshore applications. For more information, please refer to http://www.mtlo.co.jp/mo-cov/_images/top/WebsiteTerms_Active_20333287_1.pdf the contents of which are incorporated by reference into this Data Sheet.