

Table 3 a

Dimensions

SUPERMAX-TS, SUPERMAX-TS2

Imperial Unit

Pipe Body					Pin	Coupling			
Outside Diameter	Nominal Weight	Wall Thickness	Inside Diameter	Drift Diameter	Make up loss	Standard Coupling OD	Special Clearance		Length
							Special Clearance OD	Joint Efficiency	
in	lbs/ft	in	in	in	in	in	in	%	in
2-3/8	4.60	0.190	1.995	1.901	2.848	2.875	2.700	112	6.446
2-7/8	6.40	0.217	2.441	2.347	2.912	3.500	3.250	112	6.574
3-1/2	7.70	0.216	3.068	2.943	3.162	4.250	3.850	107	7.074
	9.20	0.254	2.992	2.867			3.900	103	
	10.20	0.289	2.922	2.797			4.000	113	
	12.70	0.368	2.764	2.639			4.125	113	
4	10.70	0.262	3.476	3.351	3.242	4.750	4.450	110	7.074
4-1/2	10.50	0.224	4.052	3.927	3.412	5.000	4.900	117	7.574
	11.60	0.250	4.000	3.875			4.950	117	
	12.60	0.271	3.958	3.833			4.950	108	
	13.50	0.290	3.920	3.795		5.250	5.000	112	
	15.10	0.337	3.826	3.701			5.000	97	
5	15.00	0.296	4.408	4.283	4.102	5.563	5.375	83	8.954
	18.00	0.362	4.276	4.151			5.375	69	
5 1/2	15.50	0.275	4.950	4.825	4.102	6.050	5.875	89	8.954
	17.00	0.304	4.892	4.767			5.875	81	
	20.00	0.361	4.778	4.653			5.875	69	
6 5/8	20.00	0.288	6.049	5.924	4.352	7.390	7.000	93	9.454
	24.00	0.352	5.921	5.796			7.000	72	
7	23.00	0.317	6.366	6.250	4.352	7.656	7.375	80	9.454
	26.00	0.362	6.276	6.151			7.375	70	
	29.00	0.408	6.184	6.059			7.375	63	

Note : Joint Efficiency of Regular Coupling $\geq 100\%$

Legal Notice

The use of this information is at the reader/user's risk and no warranty is implied or expressed by Metal One Corporation or its parents, subsidiaries or affiliates (herein collectively referred to as "Metal One") with respect to the use of information contained herein. The information provided on this Data Sheet is for informational purposes only, and was prepared by reference to engineering information that is specific to the subject products, without regard to safety-related factors, all of which are the sole responsibility of the operators and users of the subject connectors. Metal One assumes no responsibility for any errors with respect to this information.

Statements regarding the suitability of products for certain types of applications are based on Metal One's knowledge of typical requirements that are often placed on Metal One products in standard well configurations. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

The products described in this Data Sheet are not recommended for use in deep water offshore applications. For more information, please refer to http://www.mtlo.co.jp/mo-con/_images/top/WebsiteTerms_Active_20333287_1.pdf the contents of which are incorporated by reference into this Data Sheet.