

Table 3 b

Dimensions

SUPERMAX-TS, SUPERMAX-TS2

Metric Unit

Pipe Body					Pin	Coupling			
Outside Diameter	Nominal Weight	Wall Thickness	Inside Diameter	Drift Diameter	Make up loss	Standard Coupling OD	Special Clearance		Length
							Special Clearance OD	Joint Efficiency	
mm	Kg/m	mm	mm	mm	mm	mm	mm	%	mm
60.30	6.85	4.83	50.67	48.29	72.34	73.03	68.58	112	163.73
73.00	9.54	5.51	62.00	59.61	73.96	88.90	82.55	112	166.98
88.90	11.47	5.49	77.93	74.75	80.31	107.95	97.79	107	179.68
	13.71	6.45	76.00	72.82			99.06	103	
	15.20	7.34	74.22	71.04			101.60	113	
	18.92	9.35	70.21	67.03			104.78	113	
	15.94	6.65	88.29	85.12	82.35	120.65	113.03	110	179.68
114.30	15.65	5.69	102.92	99.75	86.66	127.00	124.46	117	192.38
	17.28	6.35	101.60	98.43			125.73	117	
	18.77	6.88	100.53	97.36			125.73	108	
	20.12	7.37	99.57	96.39		133.35	127.00	112	
	22.50	8.56	97.18	94.01			127.00	97	
127.00	22.35	7.52	111.96	108.79	104.19	141.30	136.53	83	227.43
	26.82	9.19	108.61	105.44			136.53	69	
139.70	23.10	6.99	125.73	122.56	104.19	153.67	149.23	89	227.43
	25.33	7.72	124.26	121.08			149.23	81	
	29.80	9.17	121.36	118.19			149.23	69	
168.30	29.80	7.32	153.64	150.47	110.54	187.71	177.80	93	240.13
	35.76	8.94	150.39	147.22			177.80	72	
177.80	34.27	8.05	161.70	158.75	110.54	194.46	187.33	80	240.13
	38.74	9.19	159.41	156.24			187.33	70	
	43.21	10.36	157.07	153.90			187.33	63	

Note : Joint Efficiency of Regular Coupling $\geq 100\%$ **Legal Notice**

The use of this information is at the reader/user's risk and no warranty is implied or expressed by Metal One Corporation or its parents, subsidiaries or affiliates (herein collectively referred to as "Metal One") with respect to the use of information contained herein. The information provided on this Data Sheet is for informational purposes only, and was prepared by reference to engineering information that is specific to the subject products, without regard to safety-related factors, all of which are the sole responsibility of the operators and users of the subject connectors. Metal One assumes no responsibility for any errors with respect to this information.

Statements regarding the suitability of products for certain types of applications are based on Metal One's knowledge of typical requirements that are often placed on Metal One products in standard well configurations. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

The products described in this Data Sheet are not recommended for use in deep water offshore applications. For more information, please refer to http://www.mtlo.co.jp/mo-con/_images/top/WebsiteTerms_Active_20333287_1.pdf the contents of which are incorporated by reference into this Data Sheet.