

Table 55 a (Rev.1)
Dimensions (Imperial unit)
GEOCONN-TS

Jul.-18, 2019

Pipe Body					Pin	Coupling					Length
OD	PPF	WT	ID	Drift Dia.	Make up loss	Regular	Special Clearance				
						Coupling OD	Coupling OD (Wsc1)	Joint Efficiency	Coupling OD (Wsc2)	Joint Efficiency	
inch	lbs/ft	inch	inch	inch	inch	inch	inch	%	inch	%	inch
4 1/2	10.50	0.224	4.052	3.927	3.938	5.250	5.000	100	4.875	100	8.875
	11.60	0.250	4.000	3.875			5.000	100	4.875	93	
	12.60	0.271	3.958	3.833			5.000	100	4.875	86	
	13.50	0.290	3.920	3.795			5.000	100	4.875	81	
	15.10	0.337	3.826	3.701			5.000	92	-	-	
5	15.00	0.296	4.408	4.283	4.063	5.800	5.563	100	5.375	81	9.125
	18.00	0.362	4.276	4.151			5.563	98	5.375	67	
5 1/2	15.50	0.275	4.950	4.825	4.125	6.300	6.050	100	5.875	87	9.250
	17.00	0.304	4.892	4.767			6.050	100	5.875	79	
	20.00	0.361	4.778	4.653			6.050	95	5.875	67	
	23.00	0.415	4.670	4.545			6.050	84	-	-	
6 5/8	20.00	0.288	6.424	6.299	4.313	7.390	7.000	96	-	-	9.625
7	23.00	0.317	6.366	6.241	4.500	7.875	7.656	139	-	-	10.000
	26.00	0.362	6.276	6.151			7.656	122			
	29.00	0.408	6.184	6.059			7.656	109			
	32.00	0.453	6.094	5.969			7.656	99			
	35.00	0.498	6.004	5.879			7.656	91			
	38.00	0.540	5.920	5.795			7.656	84			
7 5/8	26.20	0.328	6.969	6.844	4.688	8.500	8.125	108	-	-	10.375
	29.70	0.375	6.875	6.750			8.125	95			
	33.70	0.430	6.765	6.640			8.125	84			
	39.00	0.500	6.625	6.500			8.125	73			
8.625	24.00	0.264	8.097	7.972	4.813	9.625	9.125	134	-	-	10.625
	28.00	0.304	8.017	7.892			9.125	117			
	32.00	0.352	7.921	7.796			9.125	102			
	36.00	0.400	7.825	7.700			9.125	90			
9 5/8	36.00	0.352	8.921	8.765	4.813	10.625	10.125	101	-	-	10.625
	40.00	0.395	8.835	8.679			10.125	90			
	43.50	0.435	8.755	8.599			10.125	82			
	47.00	0.472	8.681	8.525			10.125	76			
	53.50	0.545	8.535	8.379			10.125	67			
9 7/8	62.80	0.625	9.500	9.344	4.813	10.875	-	-	-	-	10.625
10 3/4	45.50	0.400	9.950	9.794	4.813	11.750	11.250	89	-	-	10.625
	51.00	0.450	9.850	9.694			11.250	79			
	55.50	0.495	9.760	9.604			11.250	72			
	60.70	0.545	9.660	9.504			11.250	66			
	71.00	0.650	9.450	9.294			11.250	56			
13 3/8	54.50	0.380	12.615	12.459	4.813	14.375	NA	NA	-	-	10.625
	61.00	0.430	12.515	12.359			NA	NA			
	68.00	0.480	12.415	12.259			NA	NA			
	72.00	0.514	12.347	12.191			NA	NA			

Note : Joint Efficiency of Regular Coupling >=100%

Legal Notice

The use of this information is at the reader/user's risk and no warranty is implied or expressed by Metal One Corporation or its parents, subsidiaries or affiliates (herein collectively referred to as "Metal One") with respect to the use of information contained herein. The information provided on this Data Sheet is for informational purposes only, and was prepared by reference to engineering information that is specific to the subject products, without regard to safety-related factors, all of which are the sole responsibility of the operators and users of the subject connectors. Metal One assumes no responsibility for any errors with respect to this information.

Statements regarding the suitability of products for certain types of applications are based on Metal One's knowledge of typical requirements that are often placed on Metal One products in standard well configurations. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

The products described in this Data Sheet are not recommended for use in deep water offshore applications. For more information, please refer to http://www.mtlo.co.jp/mo-con/_images/top/WebsiteTerms_Active_20333287_1.pdf the contents of which are incorporated by reference into this Data Sheet.